






**TAISHIBA**  
**ELECTRIC**






Passion. Quality. Life

無  
熔  
線  
斷  
路  
器

無熔線斷路器 | NF 高啟斷系列

過負載/短路 保護兼用

框架容量(AF) 台芝型號		100 N100-HM	125 NF125-TM
外觀			
額定電流 In(A)(AT) 基準周圍溫度 40°C		15,20,30,40,50, 60,75,100	15,20,30,40,50, 60,75,100,125
額定絕緣電壓 Ui(V)		690	690
極數(P)		3	3   4
額定 啟斷 容量 (KA)	IEC 60947-2	440V	50/25
	EN 60947-2	380V	65/33
	CNS 14816-2 Icu/Ics AC	220V	100/50
外型 及 安 裝 尺 寸 (mm)		a	90   120
		b	155
		c	88
		ca	115
		bb	132
		aa	30   30

225 NF225-HM	250 NF250-TM	400 NF400-TM	630 NF630-TM	800 HF800-UM
				
125,150,175,200,225	125,150,175, 200,225,250	250,300, 350,400	500,600,630	500,630,700,800
690	690	690	690	690
3	3   4	3   4	3   4	3   4
42/21	50/25	50/25	50/25	65/33
50/25	65/33	65/33	65/33	85/43
85/43	100/50	100/50	100/50	125/63
105	105   140	140   185	210   280	210   280
165	165	257	275	275
88	88	103.5	103.5	103.5
115	115	158	158	158
126	126	194	243	243
35	35   35	44	70   70	70   70