



**TAISHIBA**  
**ELECTRIC**

Passion. Quality. Life

無  
熔  
線  
斷  
路  
器

漏電斷路器 | NVL系列、NVS系列

漏電/過負載/短路 保護兼用

框架容量(AF) 台芝型號		50 NVL-50	50 NVL-50U	50 NVL-50H				
外觀								
額定電流 In(A)(AT) 基準周圍溫度 40°C		15,20,30,40,50		15,20,30,40,50				
極數(P)		1P2線式	2P2E	1P2線式 2P2E				
額定靈敏度(mA)		30		30				
額定 啟斷 容量 (KA)	IEC 60947-2	440V		—				
	EN 60947-2	380V		—				
	CNS 5422	220V	5	5	5	10	10	15
	Icu AC	110V	5	—	10	—	15	—
外型 及 安 裝 尺 寸 (mm)		a	25	50	25	50	25	50
		b	113		113		113	
		c	61		61		61	
		ca	77.5		77.5		77.5	
		bb	120		120		120	
		aa	-	25	-	25	-	25

50 NVL-50S			50 NVL-50SU			50 NVL-50SH			30 NVS-30	50 NVS-50	
15,20,30,40,50			15,20,30,40,50			15,20,30,40,50			15,20,30	15,20,30,40,50	
1P2線式	2P2E	3P3E	1P2線式	2P2E	3P3E	1P2線式	2P2E	3P3E	2P	2P	3P
30-100-300-500可調式			30-100-300-500可調式			30-100-300-500可調式			30	30	
—			—			—			—	2.5	
—			—			—			—	2.5	
5	5		5	10		10	15		1.5	2.5	2.5
5	—		10	—		15	—		1.5	2.5	—
25	50	75	25	50	75	25	50	75	32	68.5	90.5
103			100			100			70	71	80.5
61			61			61			39	40	40
77			77			77			51	58.5	58.5
117			117			117			62	34	55
-	25	25	-	25	25	-	25	25	-	60	70