



TAISHIBA
ELECTRIC
Passion. Quality. Life

無
熔
線
斷
路
器

無熔線斷路器 | NF 系列

過負載/短路 保護兼用

框架容量(AF)		100	100	125	125	
台芝型號		NF100-CM	NF100-SM	NF125-CM	NF125-SM	
外觀						
額定電流 In(A)(AT) 基準周圍溫度 40°C		15,20,30,40,50, 60,75,100	15,20,30,40,50, 60,75,100	15,20,30,40,50, 60,75,100,125	15,20,30,40,50, 60,75,100,125	
額定絕緣電壓 Ui(V)		690	690	690	690	
極數(P)		2 3	2 3	2 3	2 3	
額定 啟斷 容量 (KA)	IEC 60947-2	440V	7.5/3.8	10/5	15/7.5	25/13
	EN 60947-2	380V	10/5	15/7.5	22/11	30/15
	CNS 14816-2 Icu/Ics AC	220V	15/7.5	25/13	30/15	50/25
外型 及 安 裝 尺 寸 (mm)		a	50 75	50 75	50 75	50 75
		b	130	130	130	130
		c	68 64	68 64	68 64	68 64
		ca	90 82	90 82	90 82	90 82
		bb	111	111	111	111
		aa	- 25	- 25	- 25	- 25

225	250	250	400	400	400	630
NF225-CM	NF250-CM	NF250-SM	NF400-CM	NF400-OM	NF400-HM	NF630-CM
125,150,175, 200,225	125,150,175, 200,225,250	125,150,175, 200,225,250	250,300, 350,400	250,300, 350,400	250,300, 350,400	500,600,630
690	690	690	690	690	690	690
2 3	2 3	2 3	2 3	2 3	3 4	3
15/7.5	15/7.5	25/13	22/11	30/15	42/21	22/11
15/7.5	22/11	30/15	25/13	42/21	50/25	35/13
25/13	30/15	50/25	35/18	65/33	85/43	35/18
107 107	107 107	107 107	140 140	140 140	140 185	210
165	165	165	257	257	257	275
72	72	72	103.5	103.5	103.5	103.5
92	92	92	158	158	158	158
126	126	126	194	194	194	243
35 35	35 35	35 35	44 44	44 44	44 44	70



TAISHIBA
ELECTRIC

Passion. Quality. Life

無
熔
線
斷
路
器

無熔線斷路器 | NF 系列

過負載/短路 保護兼用

框架容量(AF)		630	630	800	800	
台芝型號		NF630-OM	NF630-HM	NF800-CM	NF800-HM	
外觀						
額定電流 In(A)(AT) 基準周圍溫度 40°C		500,600,630	500,600,630	700,800	700,800	
額定絕緣電壓 Ui(V)		690	690	690	690	
極數(P)		3	3	3	3	
額定 啟斷 容量 (KA)	IEC 60947-2	440V	35/18	50/25	30/15	42/21
	EN 60947-2	380V	42/21	50/25	35/18	65/33
	CNS 14816-2 Icu/IcsAC	220V	65/33	85/43	50/25	85/43
外型 及 安裝 尺寸 (mm)		a	210	210	210	210
		b	275	275	275	275
		c	103.5	103.5	103.5	103.5
		ca	158	158	158	158
		bb	243	243	243	243
		aa	70	70	70	70

框架容量(AF)		1000	1250	1600	
台芝型號		NF1000-HM	NF1250-HM	FN1600-HM	
外觀					
額定電流 In(A)(AT) 基準周圍溫度 40°C		1000	1250	1600	
額定絕緣電壓 Ui(V)		690	690	690	
極數(P)		3	3	3	
額定 啟斷 容量 (KA)	IEC 60947-2	440V	85/43	85/43	85/43
	EN 60947-2	380V	100/50	100/50	100/50
	CNS 14816-2 Icu/Ics AC	220V	130/65	130/65	130/65
外型 及 安裝 尺寸 (mm)		a	210	210	210
		b	330	330	330
		c	137	137	137
		ca	191	191	191
		bb	300	300	300
		aa	70	70	70