



**TAISHIBA**  
**ELECTRIC**

Passion . Quality . Life

無  
熔  
線  
斷  
路  
器

漏電斷路器 | NV系列

漏電/過負載/短路 保護兼用

框架容量(AF)		63	100	100	100	
台芝型號		NV63-HM	NV100-CM	NV100-AM2	NV100-AM	
外觀						
額定電流 In(A)(AT) 基準周圍溫度 40°C		15,20,30,40,50, 60,63	15,20,30,40,50, 60,75,100	15,20,30,40,50, 60,75,100	15,20,30,40,50, 60,75,100	
極數(P)		3   4	3   4	3	3   4	
額定 啟斷 容量 (KA)	IEC 60947-2	440V 10	7.5	—	7.5	
	EN 60947-2	380V 15	7.5	—	10	
	CNS 5422	220V 25	10	15	15	
	Icu AC	110V 25	10	—	15	
外型 及 安 裝 尺 寸 (mm)		a	75   100	75   100	75	75   100
		b	130	130	130	130
		c	68	68	68	68
		ca	90	90	90	90
		bb	111	111	111	111
		aa	25   25	25   25	25	25   25

100	100	125	125	250	250
NV100-SM2	NV100-SM	NV125-SM	NV125-HM	NV250-CM	NV250-SM
15,20,30,40,50, 60,75,100	15,20,30,40,50, 60,75,100	15,20,30,40,50, 60,75,100,125	15,20,30,40,50, 60,75,100,125	125,150,175, 200,225,250	125,150,175, 200,225,250
3	3	3	3   4	3	3   4
—	10	15	25	15	25
—	15	22	30	22	30
25	25	30	50	30	50
—	25	30	50	30	50
75	75	75	75   100	105	105   140
130	130	130	130	165	165
68	68	68	68	68	68
90	90	90	90	92	92
111	111	111	111	126	126
25	25	25	25   25	35	35   35






**TAISHIBA**  
**ELECTRIC**

Passion. Quality. Life

無  
熔  
線  
斷  
路  
器

## 漏電斷路器 | NV系列

漏電/過負載/短路 保護兼用

框架容量(AF) 台芝型號		400 NV400-CM	400 NV400-SM	400 NV400-HM
外觀				
額定電流 In(A)(AT) 基準周圍溫度 40°C		250,300, 350,400	250,300, 350,400	250,300, 350,400
極數(P)		3   4	3   4	3   4
額定 啟斷 容量 (KA)	IEC 60947-2	22	22	42
	EN 60947-2	25	35	50
	CNS 5422	35	50	85
	Icu AC	—	—	—
外型 及 安 裝 尺 寸 (mm)	a	140   185	140   185	140   185
	b	257	257	257
	c	103	103	103
	ca	155	155	155
	bb	194	194	194
	aa	44   44	44   44	44   44
	